

RV CAMPSITE SETUP

BEFORE YOU CONNECT ANYTHING

Eight quick checks prevent the most common arrival-day mistakes

1



CHECK IN

Right campground. Right site. Right hookup type.

2



MATCH THE POWER

Read your RV rating and the pedestal: 30A, 50A, or both.

DON'T GUESS. If the service is unclear, ask campground staff.

3



FIND ALL THREE

Locate POWER, POTABLE WATER, and SEWER before parking.

4



PARK WITHIN REACH

Leave safe slack. Keep hoses and cords away from tires and traffic.

5



SECURE BEFORE UNHITCHING

Set the parking brake. Chock the wheels as your RV manual directs.

For towables: complete side-to-side leveling, then chock before unhitching.

6



LEVEL - THEN STABILIZE

Follow your RV manufacturer's sequence. Stabilizers steady - they do not lift.

Check slide-out and hitch clearance before operating them.

7



LOOK BEFORE YOU PLUG OR CONNECT

Check for scorching, looseness, cracks, leaks, water, or an open sewer inlet.

SEE DAMAGE? STOP. Do not repair it - call the campground office.

8



KEEP FRESH WATER AWAY FROM SEWER GEAR

Use separate, clearly labeled bins. Never mix hoses, fittings, or filters.

YOUR RV MANUAL OVERRIDES A GENERIC CHECKLIST

Leveling, stabilizing, slide-out, hitch, electrical, and plumbing procedures vary by RV and equipment.

Safety references: Winnebago Travel Trailer Setup & Takedown Guide and 2025 Towables Owner's Manual; KOA Full-Hookup Site and RV Hookup Guidance; Camco RV Gear Inspection Guidance.

General educational checklist. Always follow the instructions supplied with your RV and each accessory.